



TECHNICAL DATA SHEET

KEIM KS-AUFSTECKPROFIL

1. PRODUCT DESCRIPTION

Special push-on profile made of high-quality plastic with welded-on fabric flag and plaster removal edge.

2. FIELD OF APPLICATION

For attaching to KEIM Alu-Sockelprofileleiste (base boards).

For thin-layered reinforcement with approx. 6 mm plaster thickness KS-Aufsteckprofil 6.

For thick-layered reinforcement with approx. 10 mm plaster thickness KS-Aufsteckprofil 10.

3. PRODUCT PROPERTIES

- suitable for all insulation panel thicknesses and kinds
- easy to use
- fire behaviour: hardly inflammable B1 according to 4102
- non-slip
- highly weather-resistant
- long-lasting

4. APPLICATION INSTRUCTIONS

APPLICATION CONDITIONS:

Ambient and substrate temperature during application and drying must be in the range between max. 5 °C and max. 30 °C.

CONSUMPTION:

approx. 1,1 m/m

APPLICATION:

KEIM KS-Aufsteckprofil is to be applied before the application of the base coat.

REINFORCEMENT:

Apply the system's reinforcing mortar at the appropriate points and embed KEIM KS-Aufsteckprofil centrally or in the upper third, free of bubbles and folds.

The layer thickness for embedding in thin-layer systems should not be less than 2 mm and not exceed 3 mm to achieve the best possible functionality. In thick-layer systems, use close to the surface is recommended wherever possible.

AFTERTREATMENT:

After complete drying of the base coat, the surface is reinforced.

TECHNICAL DATA SHEET – KEIM KS-AUFSTECKPROFIL

5. PACKAGING

Product name	Projection	Length [m]	Pieces per unit	Content per sold unit [m]	Type of container	Length
KS-Aufsteckprofil 6	6 mm	2.50	15	37.50	carton	
KS-Aufsteckprofil 10	10 mm	2.50	15	37.50	carton	

Delivery in cartons

6. STORAGE

max. storage time	Storage conditions
no maximum storage time	dry protect against weathering flat-lying in the outer cardboard

7. DISPOSAL

Waste code: 17 09 04

8. SAFETY INSTRUCTIONS

No particular indications.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38
www.keim.com / info@keimfarben.de